

WALL

RITTENHOUSE SQUARE™

GLAZED CERAMIC





Classic Elegance

Fall in love with the time-honored look of Rittenhouse Square. This trendy, yet enduring collection has a color palette vast enough to fit any style.

• DESIGN VERSATILITY

- Subway tile that works with traditional or modern design styles
- Vast color palette works with a multitude of color schemes

· COORDINATING OPTIONS

- Coordinating brick-joint mosaic and trim available
- Colors coordinate with Modern Dimensions™ and Semi-Gloss™ and Matte™ lines, offering more design options



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information visit daltile.com.

USAGE

Floors Walls Countertops

W
C

RITTENHOUSE SQUARE™

GLAZED CERAMIC

SEMI-GLOSS





VERMILLION

ODM1 (5) ★

DM14 (4) ★

K189 (4) ★

MATTE





DECORATIVE ACCENT



SHELF RAIL (Available in Arctic White 0190, White 0100, White K101, Biscuit K175, Almond 0135, Almond K165, and Black K111)

(1), (2), (3), (4) and (5) indicate Price Groups, (1) being the least expensive. All colors available in 3 x 6 flat wall tile.

Made-to-order colors require 6-8 weeks for delivery from date of order.

- 2 x 4 brick-joint size available. Other colors (including matte finish) available via special order (not available in group 4 colors).
- Shelf Rail available
- 3 x 6 Bevel tile available; other colors available through ColorMatch™.
- Subject to crazing; black grout not recommended

Attachment A

RITTENHOUSE SQUARE™

GLAZED CERAMIC

-	7	

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
3 x 6 Wall Tile	(3" x 6") (7.60 cm x 15.20 cm)	5/16"	12.50	100
3 x 6 Bevel Wall Tile	(3" x 6") (7.60 cm x 15.20 cm)	3/8"	10.40	80
2 x 4 Brick-joint mosaic (Dot-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4"	10.00	12
2 x 6 Shelf Rail	(2-3/16" x 6") (5.50 cm x 15.20 cm)	N/A	N/A	8
	(2-3/16" x 2-3/16") (5.50 cm x 5.50 cm)	N/A	N/A	12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	√ *▲
Pool Linings	N/A	✓

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest", visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

- * Beveled and semi-gloss tile not suitable for countertops.
- ▲ Darker colors may show scratches.

TRIM

Туре	Number	Size	Pieces/ Carton
Wall Bullnose (on 6" side)	S-4369	3 x 6	100
Wall Bullnose (on 3" side)	S-4639	3 x 6	100
Wall Bullnose Corner Right	SCR-4369	3 x 6	100
Wall Bullnose Corner Left	SCL-4369	3 x 6	100
Cove Base	A-3361	3 x 6	36
Cove Base Corner Right	SCR-3361	3 x 6	36
Cove Base Corner Left	SCL-3361	3 x 6	36

INSTALLATION

Grout Joint Recommendation	Shade Variation	
Wall: 1/16" Mosaic: 1/8"	Low (V1)	

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result	Mosaic Result
Water Absorption	C373	< 20.0%	< 3.0%
Breaking Strength	C648	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	4.0-6.0	6.0-7.5
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	N/A	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at daltile.com/Factors.





